(54) WIRE-COIL PACKAGING DRUM WITH IMPROVED BOTTOM ASSEMBLY

(76) Inventors: Thomas D. Coon, Wilmington, DE (US); Randall Adoms, Van Wert, OH (US)

Courspondence Address: VORYS SATER SEYMOUR PEASE 1828 L STREET NW ELEVENTH FLOOR WASHINGTON, DC 20036

(21) Appl. No.:

69/937,282

(22) PCT Filed:

Mar. 23, 2000

(86) PCT No.:

PCT/US09/07679

Related U.S. Application Data


(60) Provisional application No. 60/126,338, filed on Mar. 26, 1999.

Publication Classification

(51) Int. Cl. 7 B65D 85/67 (52) U.S. Cl. 286/408: 206/407

(57) ABSTRACT

A game machine (Z, 200) which includes a playing field (6, 301) traversed by objects, such as balls (320). The playing field can have plural drop zones (381-383) which can be selected by the player using deflectors (108-110) that control where the balls are launched. Detectors (22, 392) indicate scoring positions assumed by the balls. A payine display (28, 335) displays accred events. A symbol selector is included to select symbols which are variably assigned to the scoring positions and displayed on displays (20, 397). The balls score symbols which can be displayed in the payline display and affect winning or bonus play. Game machine (208) includes traditional slot machine reels which works in conjunction therewith.



BEST AVAILABLE CORY 3762 P. 3

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION Interprinal Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

- (51) International Patent Classification 7:
- (11) International Publication Number:

WO 00/58181

B6SD 85/66

AI

(43) International Publication Date:

5 October 2000 (05.10,00)

- (21) International Application Number:
- PCT/US00/07679
- (22) International Filing Date:
- 23 March 2000 (23.03.00)
- (30) Priority Data:
 - 60/126,338

26 March 1999 (26,03.99)

ШS

- (71) Applicant (for all designmed Super except US): GREIP BROS. CORPORATION [US/US]: 425 Winter Road, Delaware, OH 43015 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): COON, Thomas, D. [US/US]; Graif Bros. Corporation, 425 Winter Read, Delaware, OH 43015 (US). ADAMS, Revoluti (US/US); Greff Bros. Corporation, 425 Winter Road, Delaware, OH 43015 (US).
- (74) Agents: SHAPIRO, Mitchell, W. et al., Vorys, Sator, Seymour and Pease LLP, 11th Scor, 1828 L Street N.W., Washington, DC 20036 (US).

(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM. DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, IP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patow (AM, AZ, BY, KG, KZ, MI), RU, TJ, TM), European pasent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF. CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TO).

Published

With international search report.

BEST AVAILABLE COPY

(54) THE: WIRE-COIL PACKAGING DRUM WITH IMPROVED BOTTOM ASSEMBLY

(57) Abstract

£

An improved wire-cell packaging dram com-prints a dram (IOA) with a bottom leading (60) hav-ing a hole (62), and an anchoring member mounted to the bottom heading (60) and cooperating with the hole (62) such that an uncharring portion (76) of the anchoring member (70) is disposed to suctor a hold-down system for a wire coil received in the drum. The anchoring monaber may comprise a susp-mounted plug that is conveniently inserted into the hole (62) of the bottom heading (60), with the hold-down system comprixing an elastic loop, such as a rebber band (80), which may be secured to the plug by a cable ris (82) or the libra.

